



Art. No. 4B7-021-38

Article Name. Crowd Control Barrier (type A leg)
(available in two type)

| Article No. | Length | Width. | Bar. | Weight. | Finish. |
|-----------------|-----------|-----------|------|---------|----------|
| 4B7-021-38 Typ1 | 1.1 meter | 2,2 meter | 16 | 18.0 kg | Post HDG |
| 4B7-021-38 Typ2 | 1.1 meter | 2.5 meter | 18 | 20.0 kg | Post HDG |

Article Information. Main frame, below center frame and leg made with pipe Ø38 x 1.6 thickness and bars with pipe of Ø16 x 1mm thickness

Shipping. Either 576 of Typ2 or 720 Typ1 qty stuffed in 40Ft Hi Cube container and delivered in cross Europe in 8 to 11 weeks.

Standard Information

Raw Material Grade

- a. Plates – S355 J2HR eh ≥ 395 N/mm²
- b. Pipes – S235 JRH.

Welding Consumable

- c. Gas – Make Linda, mixture of Cargon 18 MCP with mixture of Argon 82% + Co2 18%
- d. Wire – from CE certified supplier (Filler wire according to EN ISO 14341:2011)

Welding Standard

- e. Welding according to – EN ISO 3834-3:2006 (Part 3: standard quality requirements)
- f. Welding process according to – DIN EN ISO 4063:2001 – 135 metal active gas welding (MAG)
- g. Qualification test of welding according to – EN287-1:2004

Hot Dip Galvanized

- h. According to ISO1461