



Art. No. 4B7-032 (With foot)

Article Name. Crowd Control Barrier
(available in two type)

Article No.	Width.	Bar.	Weight.	Finish.
4B7-032 Typ1 (with foot)	2.2 meter	14	19.0 kg	Post HDG
4B7-032 Typ2 (with foot)	2.5 meter	19	21.5 kg	Post HDG

Article Information. Main frame, below center frame and leg made with pipe Ø33 x 1.6 thickness and bars with pipe of Ø16 x 1mm thickness. With 3M Adhesive Reflective (EN12899)

Shipping. Either 576 of Typ2 or 720 Typ1 qty stuffed in 40Ft Hi Cube container and delivered in cross Europe in 8 to 11 weeks.

Standard Information

Raw Material Grade

- a. Plates – S355 J2HR eh ≥ 395 N/mm²
- b. Pipes – S235 JRH.

Welding Consumable

- c. Gas – Make Linda, mixture of Corgon 18 MCP with mixture of Argon 82% + Co2 18%
- d. Wire – from CE certified supplier (Filler wire according to EN ISO 14341:2011)

Welding Standard

- e. Welding according to – EN ISO 3834-3:2006 (Part 3: standard quality requirements)
- f. Welding process according to – DIN EN ISO 4063:2001 – 135 metal active gas welding (MAG)
- g. Qualification test of welding according to – EN287-1:2004

Hot Dip Galvanized

- h. According to ISO1461