

Art. No. 4B7-032

Article Name. Crowd Control Barrier (available in two type)

Article No.	Width.	Bar.	Weight.	Finish.
4B7-032 Typ1	2.2 meter	14	14.0 kg	Post HDG
4B7-032 Typ2	2.5 meter	19	16.5 kg	Post HDG

Article Information. Main frame, below center frame and leg made with pipe $\emptyset 33 \times 1.6$ thickness and bars with pipe of $\emptyset 16 \times 1$ mm thickness. With 3M Adhesive Reflective (EN12899)

Shipping. Either 576 of Typ2 or 720 Typ1 qty stuffed in 40Ft Hi Cube container and delivered in cross Europe in 8 to 11 weeks.

Standard Information

Raw Material Grade

- a. Plates S355 J2HR eh \geq 395 N/mm².
- b. Pipes S235 JRH.

Welding Consumable

- c. Gas Make Linda, mixture of Corgon 18 MCP with mixture of Argon 82% + Co2 18%
- d. Wire from CE certified supplier (Filler wire according to EN ISO 14341:2011)

Welding Standard

- e. Welding according to EN ISO 3834-3:2006 (Part 3: standard quality requirements)
- f. Welding process according to DIN EN ISO 4063:2001 135 metal active gas welding (MAG)
- g. Qualification test of welding according to EN287-1:2004

Hot Dip Galvanized

h. According to ISO1461

www.navastrid.de